

Specifications ABI Alucable DeLuxe Combination



SPECIFICATIES	
Height aluminium	16 mm
Width aluminium	50 mm
Thickness aluminium	1,75 mm
Profile distance	4 mm
Connection profiles	Stainless steel cable 2 mm, with EPDM distance cups
Bottom profiles	Sound-damping and anti-slip layer
Standard colour aluminium	Brute
Optional	Anodizing in 24 colours
Max load	2.100 kg per 100 cm ²
Classification of burning behaviour	B _{fl} -s1
Classification of slip-resistance	R10
Total weight of mat	approx. 21 kg / m ²
Total height of mat	<u>Inlays:</u> Brushes: 22 mm Needle punch: 21 mm Rubber: 21 mm Carpet: 20 mm

OPTIONS INLAYS		
Brushes	100% nylon 6.6 colour-solid	Colours: B01 Black B09 Mint green B02 Dark grey B10 Blue B03 Light grey B11 Dark red B04 Brown B12 Red B05 Yellow B13 Orange B06 Tan B14 Purple B07 Dark Green B15 White B08 Green B16 Light blue
Rubber	EPDM rubber with ribbed structure	Colour: black
Needle punch	100% polypropylene	Standard colours: black, grey and cocos <i>Other colours are possible</i>
Carpet	100% polyamide	Standard colours: 007 anthracite 014 grey 016 grigio 052 graphite 070 sand 071 taupe uni <i>Other colours are also possible</i>