

ABI CARPET LOGOMAT



SPECIFICATIONS			
Yarn:	Continuous filament PET yarn with 100% post-consumer recycled content		
Weight:	900 gr / m ²		
Pile height:	11mm		
Static control:	ISO 6356 (2012) Determination of the static electrical propensity Walking test: -0.3 KVolts Satisfies IBM test requirements		
T. 1 . 1 .			
Total weight:	Approx. 2.9 kg / m2		
Total height:	Approx. 7 mm		
Primary backing:	Freudenberg Lutradur™ Polyester Spun bound		
	Non-woven Fabric 130 gr / m ²		
Rubber backing:	100% Nitrile EXS [™] rubber for maximum oil resistance, weight reduction and flexibility. Compression molded with reinforced borders on all four sides Border Thickness : 2.5 mm Body Thickness : 1.5 mm		
Border width:	2 cm		
Size variance:	+/- 2%		
Flammability:	Passes BS 4790 (1987) determination of the flammability of textile floor coverings: Low radius of effects of ignition.		

STANDARD SIZES (cm)				
60 x 85	85 x 300	115 x 250	150 x 250	
75 x 85	115 x 180	115 x 300	150 x 300	
85 x 115	115 x 200	150 x 200	200 x 200	
85 x 150	115 x 240	150 x 240	200 x 300	
Special shapes and sizes are also available. Maximum size: 200 x 550 cm.				
Ask our sales team for the options.				



COLOURS

66 different colours

